

PRODUCT BRAND NAME	M0220-00 WHITE	TD30AM022000R1
	MICCA ACRYLIQUE + ®	
	SURFACE TOLERANT DIRECT TO METAL WATER BASE	

RELATED PRODUCTS	M0220-20 : Medium Base	M0229-00 Red Oxide
	M0220-60 : Accent Base	
	M0223-00 : Black	

DESCRIPTION
A coating based on acrylic resin which has good adhesion to most common construction materials (ferrous and non ferrous metals). Can be applied directly over rusted steel with minimum surface preparation (wire brushing). It offers a high level of corrosion resistance and to microbial attack. It is resistant to flash rusting and fast drying to form a tough long lasting film.
USAGE
Recommended for interior and exterior use for direct application on cleaned and rusted steel with a minimum of surface preparation (wire brushing).
SURFACE PREPARATION
Surfaces to be painted must be clean, dry and free from wax, grease, loose dry paint and other surface contaminants. On rusted steel, wire brushing is usually sufficient, provided all loosely adhering rusts/scales are removed.

STORAGE
Store in a cool dry place. Keep from freezing.
DIRECTIONS FOR USE
Stir well before using. Apply at temperature between 10 – 30 °C using a brush, roller or spray equipment. For best results, two coats are recommended. Clean tools with tap water.
SAFETY MEASURES
May irritate eyes. Do not get into eyes. Keep out of reach of children. FIRST AID TREATMENT : Contains small amounts of amino methyl propanol. If in eyes, rinse well with water. If swallowed, call poison control center or doctor immediately

TECHNICAL INFORMATION		
Viscosity (White)		63 ± 3 KU.
Gloss		15 ± 2 @ 60°
Colour		White & range of colors
Coverage		609 ft ² /gal-mil (white)
Dry to touch		1 h. (25° c)
Time to recoat		2 h.(25°c)
Solid weight		54 ± 1%
Solid volume		39 ± 1%
VOC		< 150 g/l

Revision 02: June 09, 2009	F4.04-P104-04 04-08-10
----------------------------	---------------------------