


PRODUCT BRAND NAME NAME	M0260 SERIES "Designer" Low Voc (100)	TD35M0260R2
	MICCA ACRYLIQUE + ®	
	SATIN ACRYLIC	

RELATED PRODUCTS	M0260-00 WHITE	M0260-10 PASTEL	M0260-20 MEDIUM	M0260-40 DEEP
	M0260-60 ACCENT	M260-70 RED BASE	M260-80 YELLOW BASE	

DESCRIPTION
A coating based on 100% acrylic emulsion which produces a durable and flexible satin finish. Adheres well over chalky surfaces. It is spatter resistant, low odor, easy to apply and clean up.
USAGE
Recommended for interior and exterior surfaces such as: drywall, wood, cement, brick, siding or primed metal.
SURFACE PREPARATION
Surfaces to be painted must be clean, dry, void of old flaking paint and free of all contaminants. Repair cracks with mortar or mastic. Seal wood knots and sap streaks with shellac. It is recommended that all surfaces be primed with the recommended primer.

STORAGE
Store in a cool, dry place. Store at a temperature between 5°C - 30°C. Keep from freezing.
DIRECTIONS FOR USE
Stir well before using. Do not thin this product. Apply at a temperature between 10-30° Celsius, using a brush roller or spray equipment. One coat will usually suffice on primed surfaces. Clean tools using warm, soapy water.
SAFETY MEASURES
May irritate eyes. Do not get into eyes. Keep out of reach of children. FIRST AID TREATMENT : Contains small amount of amino methyl propanol. If in eyes rinse well with water. If swallowed call poison control center or doctor immediately.

TECHNICAL INFORMATION (Information based on white : M0260-00)																					
Environmental Choice Program : Compliant to latest ECP regulations : CCD - 47 Low VOC : 100 g/L* max *Addition of colorants may increase Voc. Formulated without lead, mercury and chromates. Approved for Construction Materials, Packaging Materials and Non-Food Chemical Products.  Dry Time : Can vary according to temperature, relative humidity and porosity of substrate. Coverage : Based on theoretical coverage i.e. no losses. Actual coverage may vary according to application method, texture & porosity of substrate. Washability : Allow at least 30 days before heavy washing	<table border="1"> <tr> <td>Viscosity</td> <td>98 ± 3KU.</td> </tr> <tr> <td>Gloss</td> <td>6 -9° @ 60</td> </tr> <tr> <td>Coverage (white)</td> <td>11-13 m² / L (474 - 560 ft²/gal)</td> </tr> <tr> <td>Dry to touch</td> <td>1 hr.</td> </tr> <tr> <td>Time to recoat</td> <td>2-3 hr.</td> </tr> <tr> <td>B.N.Q.</td> <td>3712-001 Type, Type A, Class 3, Grade 1</td> </tr> <tr> <td>Solid weight</td> <td>55.39 ± 1 %</td> </tr> <tr> <td>Solid volume</td> <td>38.50 ± 1 %</td> </tr> <tr> <td>Ecologo</td> <td>CCD - 47 (new regulation)</td> </tr> <tr> <td>VOC</td> <td>100 g / l max</td> </tr> </table>	Viscosity	98 ± 3KU.	Gloss	6 -9° @ 60	Coverage (white)	11-13 m ² / L (474 - 560 ft ² /gal)	Dry to touch	1 hr.	Time to recoat	2-3 hr.	B.N.Q.	3712-001 Type, Type A, Class 3, Grade 1	Solid weight	55.39 ± 1 %	Solid volume	38.50 ± 1 %	Ecologo	CCD - 47 (new regulation)	VOC	100 g / l max
	Viscosity	98 ± 3KU.																			
	Gloss	6 -9° @ 60																			
	Coverage (white)	11-13 m ² / L (474 - 560 ft ² /gal)																			
	Dry to touch	1 hr.																			
	Time to recoat	2-3 hr.																			
	B.N.Q.	3712-001 Type, Type A, Class 3, Grade 1																			
	Solid weight	55.39 ± 1 %																			
	Solid volume	38.50 ± 1 %																			
	Ecologo	CCD - 47 (new regulation)																			
VOC	100 g / l max																				

RECOMMENDED PRIMERS

Dry Wall/Plaster Acoustic tiles:	M0170-00 White Latex Primer and Sealer or M0175-00 Super Adhesive Acrylic Primer and Sealer
Wood: knots and sap streaks bare wood	Shellac and primer M0470-00 Alkyd Undercoat
Masonry: smooth: rough	M0170-00 White Latex Primer and Sealer or M0175-00 Super Adhesive Acrylic Primer and Sealer M0102-00 Block Filler
Ferrous Metal	M0475-00 Alkyd Undercoat for Metal M0220-00 Series, Acrylic Primer DTM White, Black, Red and tint bases
Aluminium and Galvanized steel:	M0271-00 Acrylic Primer for galvanized steel and aluminium
Stain Bleeding:	M0472-00 Low Odor Stain Blocking or M0272-00 White Acrylic Primer for Stain Blocking

Colour: White & Tint Bases

Sizes : 18.9 L : 3.78 L : 0.946 ml