

**DESCRIPTION:**

An interior/exterior coating based on 100% acrylic emulsion, which produces a durable and flexible satin finish. Adheres well over chalky surfaces. It is spatter resistant, low odor, easy to apply and clean up. Contains anti-bacterial biocides, anti-mold fungicide and mildewcide, and is suitable for kitchen and bathrooms.

**RELATED PRODUCTS :**

**M0260-00 WHITE -- M0260-10 PASTEL--M0260-20 MEDIUM--M0260-40 DEEP  
M0260-60 ACCENT --M260-70 RED BASE--M260-80 YELLOW BASE**

**COLOURS:** White & Tint Bases

Addition of colorants may increase Voc. Formulated without lead, mercury and chromates.

**USAGE:**

Recommended for interior and exterior surfaces such as: drywall, wood, cement, brick, siding or primed metal.

**DIRECTIONS FOR USE:**

Stir well before using. Do not thin this product. Apply at a temperature between 10-30° Celsius, using a brush roller or spray equipment. One coat will usually suffice on primed surfaces. Clean tools using warm, soapy water.

**SURFACE PREPARATION:**

Surfaces to be painted must be clean, dry, void of old flaking paint and free of all contaminants. Repair cracks with mortar or mastic. Seal wood knots and sap streaks with shellac. It is recommended that all surfaces be primed with the recommended primer.

**PRIMERS RECOMMENDED:**

Dry Wall/Plaster M0170-00 White Latex Primer and Sealer or M0175-00 Super

Acoustic tiles: Adhesive Acrylic Primer and Sealer

Wood: Nodes and veins: Seal with shellac followed by primer

New: M0470-00 Alkyd Primer

Masonry

Soft: M0170-00 White Primer or super adherent

M0175-00 Acrylic Primer

Textured: M0102-00 Block Filler Filler Concrete

Ferrous Metal:

Primer for metal M0475-00 M0220-00 Series solvent acrylic based primer  
white water, black, red and tint.

Aluminum and: M0271-00 Acrylic Latex Primer for galvanized steel and aluminum.  
galvanized metal

Bleeding stains: M0472-00 Alkyd mask low odor stain

M0274-00 White Acrylic Primer for masking stains

**LIMITATIONS:** Avoid painting if the relative humidity exceeds 85%.

**Appearance:** White

**Odor:** Mild

**Gloss :** 6-9 % @ 60°

**Viscosity:** 97 ± 3 KU

**DENSITY:** 1.354 ± 0.030

**pH:** 8 - 9

**Composition:**

**RESIN TYPE:** Acrylic emulsion

**PIGMENT TYPE:**

Titanium Dioxide.

**SOLVENTS:** Water and ethylene Glycol

**Volatile Organic Compounds:** max 92 g/L

**Weight per Gallon:**

11.30 ± .25 lbs

**Solids by weight :** 52 ± 1%

**Solids by volume:** 35 ± 1%

**Recommended Dry Film**

**Thickness (DFT):** 1- 1.5 mils or 25.0-37.5 microns, per coat (Two coats are recommended).

**Wet Film to Achieve (WFT):**

2.8 - 4 mil

**Coverage:** 10- 15 m<sup>2</sup> / L

( 400 - 594 ft<sup>2</sup>/gal )

**Dry times:** Drying time may be longer depending on humidity, temperature variation, texture and surface porosity.

**Dry touch:** 1 Hr depending on temperature & humidity

**Time to recoat :** 2-3 hr

**Shelf life:** 1 year, in unopened containers properly stored in a cool dry area.

**Handle:** 1/2 Hr

**Humidity:** 50%. Maximum: 85%

**SURFACE CLEANING:**

Allow at least 30 days before heavy washing. Avoid abrasive cleaning agents or excessive scratching

**STORAGE:**

Keep this product in a cool, dry, ventilated area between 15 ° C and 25 ° C. Keep containers closed when not used. To avoid freezing.

**THINNING:**

The product is ready for use without dilution. If necessary, 10% dilution.

**COVERAGE:**

Based on theoretical coverage i.e. no losses. Actual coverage may vary according to application method, texture & porosity of substrate.

**DRY TIME :**

Can vary according to temperature, relative humidity and porosity of substrate.

**SAFETY INFORMATION**

Flashpoint: None

Lead: None

Mercury: None.

**WARNING!**

May cause eye irritation if in direct contact to eyes. May be harmful in contact to skin. May be harmful if inhaled. May be harmful if swallowed.

Wear protective clothing, gloves, eye, and face protection.

Do not eat, drink or smoke when using this product.

Do not breathe dusts. During sanding. Wash hands thoroughly after handling. Keep out of reach of children.

If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. If on skin: Wash with plenty of soap and water.

**If swallowed:** Rinse mouth. **DO NOT INDUCE VOMITING.** Immediately call a **POISON CENTER/Doctor.**

**WASTE DISPOSAL:**

Reach your municipality about proper disposal procedure or give leftover paint to someone who could use it, a neighbor or friend, a recreational service or a non-profit organization. For more information, visit [www.eco-peinture.ca](http://www.eco-peinture.ca) if you reside in Quebec. Do not leftover paint down the drain.

**APPLICATION:**

Temperature (°C): 15 to 30 °C  
(59° to 86 °F)

**Packaging:** Size (White & Tint Bases 18.9 L : 3.78 L : 0.946 ml)  
Other bases: 3,78L & 946ml.

**Equipment Recommendations**  
(Comparable Equipment Also Suitable).

**Brush:** Use a nylon / polyester brush

**Roller:** Use a 3/8" a -3/4" nap synthetic roller cover.

**SPRAY-Airless** (filter through cheesecloth when the Airless paint sprayer is used)

Pressure 2000-2500 psi

Tip: 0.015. – 0.017.



**SPECIFICATIONS**

Environmental Choice Program: Compliant to latest ECP regulations: CCD - 47

Low VOC: 100 g/L\* max. Addition of colorants may increase Voc.

Formulated without lead, mercury and chromates.

Approved for Construction Materials, Packaging Materials and Non-Food Chemical Products.

**PHYSICAL Properties** (Calculated values are shown and may vary slightly from the actual manufactured material).

**WARRANTY:**

In lieu of all other warranties or guarantees, express or implied, by contract or law, manufacturer's liability hereby limited to replacement of the merchandise herein if found to be defective upon inspection by it. Manufacturer shall no be liable for any representations, warranties (express or implied) made by any of its agents, representatives or employees regarding the merchandise or product contained herein.