

PRODUCT	M0275-00 Low Voc (100)	TD40M027500R1
BRAND NAME	MICCA ACRYLIQUE + ®	
NAME	PEARL ACRYLIC MILDEW PROOF WHITE	

RELATED PRODUCTS

DESCRIPTION

A coating based on a 100% acrylic emulsion formulated to resist discoloration from mildew and moisture, in bathrooms and humid areas. It is spatter resistant, low odor, easy to apply and clean up.

USAGE

Recommended for interior & exterior surfaces as a primer / topcoat on drywall, wood, cement, and brick siding to provide mildew resistance. On steel, it should be applied over the recommended primer. Can be used alone or top coated with mildew resistance alkyd or latex paint. Over previously painted glossy surface, light sanding is recommended. Seal knots and sap streaks with shellac. For better results, apply 2 coats.

SURFACE PREPARATION

Surfaces to be painted must be clean, dry and free from all contaminants. Neutralize existing mildew with household bleach. Clean excess dirt or residue with household cleanser (TSP). Rinse well. Some stains may require a second cleaning or solvent clean.

STORAGE

Store in a cool dry place. Store at a temperature between 5°C - 30°C. Keep from freezing.

DIRECTIONS FOR USE

Stir well before using. Do not thin this product. Apply at temperature between 10 - 30°C using a brush, roller or spray equipment. One coat will usually suffice to obtain uniform results. Clean tools with warm, soapy water.

SAFETY MEASURES

May irritate eyes. Do not get into eyes. Keep out of reach of children.

FIRST AID TREATMENT:

Contains small amount of amino methyl propanol. If in eyes rinse well with water. If swallowed call poison control center or doctor immediately. Do not induce vomiting

TECHNICAL INFORMATION

<p>Environmental Choice Program :</p> <p>Compliant to latest ECP regulations : CCD - 47</p> <p>Low VOC : 100 g/L* max</p> <p>*Addition of colorants may increase Voc.</p> <p>Formulated without lead, mercury and chromates.</p> <p>Dry Time :</p> <p>Can vary according to temperature, relative humidity and porosity of substrate.</p> <p>Coverage : Based on theoretical coverage i.e. no losses. Actual coverage may vary according to application method, texture & porosity of substrate.</p> <p>Washability :</p> <p>Allow at least 30 days before heavy washing.</p>	Viscosity	98± 3 KU.
	Gloss	18 ± 3° @ 60
	Colour	White
	Coverage	574 ft ² /gal-mil
	Dry to touch	1 h.
	Time to recoat	2-3 h.
	C.G.S.B	1 GP 1.195 Type
	B.N.Q.	3712-001 Type, Type A, Class 3, Grade 1
	Solid weight	52.42 ± 1%
	Solid volume	37.21 ± 1%
Ecologo	CCD - 47 (new regulation)	
VOC	100 g / L max	

RECOMMENDED PRIMERS

Wood: knots and sap streaks bare wood	Shellac and primer M0275 - 00
Masonry: smooth: rough	M0275-00 M0102-00 Block Filler (depending on degree of roughness) followed by M0275-00
Ferrous Metal	M0475-00 Alkyd Undercoat for Metal M0220-00 Series, Acrylic Primer DTM White, Black, Red and tint bases
Aluminium and Galvanized steel:	M0271-00 Acrylic Primer for galvanized steel and aluminium
Stain Bleeding:	M0472-00 Low Odor Stain Blocking or M0272-00 White Acrylic Primer for Stain Blocking

Colour: White.

Sizes : 3.78 L : 946 ml