

PRODUCT	M0801-00	TD67AM080100R5
BRAND NAME	MICCA ACRYLIC SEALER	
NAME	MANSONRY & UNI-STONE SEALER	

RELATED PRODUCTS	M0801-30% M0801-40%
-------------------------	---------------------

DESCRIPTION

Clear acrylic sealer for uni-stones or concrete with excellent exterior durability. It is fast drying with excellent hardness, good chemical and abrasion resistance. A high gloss finish that enhances and preserves the natural beauty of uni-stone or concrete for long periods of time.

USAGE

Recommended for exterior use on all porous surfaces such as: concrete stone, brick and cement to protect against damaging effects of water, sunlight (UV), chemicals, petroleum spills and de-icing salt.

SURFACE PREPARATION

The surfaces to be coated must be clean, dry, void of old flaking paint and free from all other contaminants. Any efflorescence must be cleaned with dilute muriatic acid, then rinsed very well with water and surface must be completely dry before coating..

DIRECTIONS FOR USE

Stir well before using. Apply at a temperature between 10-30° Celsius, using brush, roller or spray equipment. For a Wet Look apply two coats. Do not apply too thick in single coat as it may cause premature failure. Clean equipment with Micca Thinner M0063-00.

STORAGE

Store in a cool, dry place. Store at a temperature of 5°C - 30°C.

FIRST AID & SAFETY MEASURES

Keep out of reach of children. Can irritate eyes if in contact.
FLAMMABLE LIQUID AND VAPORS. Keep away from sparks and open flame.
 If swallowed DO NOT INDUCE VOMITING and obtain medical assistance immediately.

TECHNICAL INFORMATION

<p>New cement should be aged for one month before coating.</p> <p>Do not apply when rain is imminent within 36 hours.</p>	Gloss	Semi-gloss or high gloss depending on surface
	Color	Translucent
	Coverage	450 sq ft./gal-mil
	Dry to touch	15 min.
	Hard Dry	12 hours @ 25 °C
	Flash Point (T.C.C.)	- 18 °C
	Solid weight	20 ± 1%
	Solid volume	15 ± 1%
	VOC	< 400 g/L