

**M0880-00 MICCA MASON SEALER@WHITE CONCRETE ACRYLIC SEALER**

**DESCRIPTION**

A concrete sealer based on acrylic resin designed to give protection to concrete. It is offered in a range of color, fast drying and resistant to ultraviolet and most chemicals. It forms a hard film for excellent sealing properties.

**RELATED PRODUCTS:**

M880-00 WHITE—M880-20 WHITE TINTING BASE- M880-21 WHITE TINTING BASE WITH COLOR— M880-60 ACCENT BASE- M880-61 ACCENT BASE COLORED

**USES:**

Recommended for interior/exterior use on all porous surfaces such as; concrete stone, brick and cement. Most suitable for use in parking garages, pavements, exposed aggregate concrete & industrial concrete floors.

**SURFACE PREPARATION:**

The surfaces to be painted must be clean, dry, void of old flaking paint and free from all other contaminants. Any efflorescence must be cleaned with dilute muriatic acid, and then rinsed well with tap water. It is recommended that new cement be aged for one month before

coating.

**DIRECTIONS FOR USE:**

Stir well before using. Apply at a temperature between 10-30 °C, using a brush, roller or spray equipment. Clean tools with M0061-00. WORK AREA MUST BE WELL VENTILATED.

**STORAGE:** Keep the product in a dry and cool area. Keep away from open flames and sparks. The storage temperature is : (5- 30) °C.

**THINNING:**

Do not thin. Because this product is quick drying, keep container closed when not in use.

**LIMITATIONS:**

Do not apply when air and surface temperatures are below 50° F (10° C).

**SAFETY INFORMATION:** Lead: None.

**DANGER.** Highly flammable liquid and vapour. Causes mild skin irritation. May be fatal if swallowed and enter airways. May cause cancer. May cause genetic defects. May cause respiratory irritation. May cause drowsiness or dizziness.

Wear protective eyewear, waterproof gloves, and protective clothing.

Store locked up. Keep cool. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.

If in eyes: Rinse cautiously with water for several minutes and

remove contacts if present and easy todo. Continue rinsing and get medical attention if eye irritation persists.

**Color:** White

**Gloss/ Sheen:** 23 ± 5°

**PH :** NA

**Viscosity :** 55 ± 3 KU

**Density:** 1.130 ± 0.05

**Odor:** Strong

Vehicle Type: Acrylic Resin

Volatile Organic Compounds (VOC) 494 Grams/Liter 4.12 lbs./Gallon

**Flash point:** 22° C

**Weight per Gallon:**

7.06 ± 0.25% lb/gal.

**Solids by weight:** 40 ± 1%

**Solids by volume:** 37 ± 1%

**Film Thickness:**

**Wet (WFT) :** 3-4 mils

**Dry (DFT):** 1.0-1.5 mils, 25.0-37.5 microns,

**Theoretical coverage:**

396-593sq ft/gal, 10-14 m<sup>2</sup>/L, @1-1.5 mils DFT

**Practical coverage:**

(At an efficiency of 85%)

The coverage is 336-505 sq ft / gal, 9-12 m<sup>2</sup> / L @ 1-1.5 mils DFT dry film thickness)

**Dry Time @ 77° F (25° C) @ 50% RH**

**To touch:** 1 Hour

**To recoat:** 3 Hours

**Packaging:**

Available sizes: 18,9 L, 3,79 L, 946 ml & 200 L .

**Application**

*Temperature (°C):* 10 to 30 °C (50° to 86 °F)

Humidity: Ideal: 50%. Maximum: 65%.

## M0880-00 MICCA MASON SEALER@WHITE CONCRETE ACRYLIC SEALER

If on skin: Wash with plenty of soap and water.

If Inhaled: Remove person to fresh air and keep comfortable for breathing

**If swallowed: Rinse mouth and get medical attention if you feel unwell.**

**Do not induce vomiting.**

Consult the form of safety data (SDS) and an other information on label before using this product.

**PHYSICAL PROPERTIES:**

The values shown are theoretical and may vary slightly from the finished product.

**WASTE DISPOSAL:**

Reach your municipality about proper disposal procedure or give leftover paint to someone who could use it, a neighbor or friend, a recreational service or a non-profit organization. For more information, visit [www.eco-peinture.ca](http://www.eco-peinture.ca) if you reside in Quebec. Do not leftover paint down the drain.

**WARRANTY:**

In lieu of all other warranties or guarantees, express or implied, by contract or law, manufacturer's liability hereby limited to replacement of the merchandise herein if found to be defective upon inspection by it. Manufacturer shall no be liable for any representations, warranties (express or implied) made by any of its agents, representatives or employees regarding the merchandise or product contained herein.

**Equipement Recommendation**  
(Comparable Equipment Also Suitable).

**Brush:** Use a nylon / polyester brush

**Roller:**

**AIRLESS SPRAY :**

(filter through cheesecloth when the Airless paint sprayer is used)

Fluid Pressure: 1,500 – 2500PSI;  
Tip .011 - .013 Orific .

